St. Leo

# PRODUCT SHEET: ORIGINAL PIGMENTS – ESSENTIAL INTENSE MATTE

## PRODUCT DESCRIPTION:

Crafted from premium ingredients for true colour representation with a completely matte finish from all angles. Essential Intense Matte is waterborne and low-VOC to provide a conscious covering for children's rooms and living spaces. With a thick consistency, Essential Intense Matte provides high coverage, fast and easy application and a wipeable finish.

## PHYSICAL / CHEMICAL DATA

| | |
|---|---|
| Usage: | Interior walls and ceilings |
| Binder: | Copolymer dispersion |
| Gloss: | 2 - matte |
| Drying time: | at 23 ° C / 50% RH: 2 hours.<br>Recoat after 6 hours |
| Application Temp: | Min + 5°C. Max + 25°C |
| Humidity: | 40-80% RH (65% RH optimal) |
| Tools: | Brush, roller, spray |
| Dilution: | Water. Max. 10% |
| Bases: | Base Clear, Base White |
| Package Sizes: | 10L,5L, 2,5L, 100ML |
| Cleaning: | Water |
| Storage: | Frost-free |
| MAL Code: | (1993): 00-1 |
| EU VOC Limit Value: | (cat. A/a): 30g/l (2010).<br>Contains max. 2g/l VOC |

This declaration applies to the colour white. The figures may vary for other colours.

## DETAILS

Application:
Surfaces must be clean, dry, smooth and not transmit any loose particles. Untreated plaster, concrete and common construction boards must be primed before painting. Previously painted surfaces should be washed and degreased before painting. For best results, apply 1-2 coats of primer before applying 2 coats of paint. Stir the paint thoroughly before use. Drying time: approximately 6 hours at 23°C and 50% RH. Please follow full application instructions available at stleointeriors.com.

Coverage:
Approximately 6–8 M2 / Litre.

Storage & Waste:
Always store in original packaging. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Storage temperature: Frost free. All paint residues and containers must be deposited at your local waste collection point.

CONTACT
+45 53740622
INFO@STLEOINTERIORS.COM
STLEOINTERIORS.COM